



MADE FOR  
NEW ZEALAND  
SINCE 1934

SAFETY

# WILDCAT 3.0

UPPER: BULLHIDE LEATHER | COLOUR: BLACK | **4998**

HEAVY INDUSTRIAL ENVIRONMENTS

ZIP SIDE

WIDE FITTING

HEIGHT | 150mm

SIZE: 4-14



CUSHION  
CORE 3.0



STEEL  
TOE CAP



STEEL  
TOE CAP



PENETRATION  
RESISTANT



WATER  
RESISTANT  
LEATHER



300°C  
RESISTANT



SLIP  
RESISTANT



OIL/ACID  
RESISTANT



ORGANIC  
FAT/OIL  
RESISTANT



ELECTRICAL  
HAZARD  
RESISTANT



COOLMAX  
LINING



CUSHION  
CORE 3.0

For those who walk on the wild side—the Wildcat 3.0 is tough, durable and comfortable, with our tried and tested CushionCore 3.0 comfort technology to tame any worksite.

- Revolutionary world-first CushionCore 3.0 comfort technology combines two compounds of PU injected into the midsole providing superior shock absorption at the heel while also providing rebound at the forefront as you step
- Nitrile Rubber outsole with aggressive self-clearing tread pattern providing superior grip, stability and abrasion resistance. Rubber outsole increases cut and slip resistance and is resistant to hydrolysis and microbial attack
- Super cushioning Comf2Bull Quad-Max footbed of a soft PU with a cushioning heel that's also antibacterial and washable
- Black water-resistant Bullhide leather with orange High-Vis stitching
- Coolmax® lining fabric helps transport moisture away from your foot, through the fabric, where it can evaporate quickly
- Broad fitting 200 joule impact resistant Type 1 steel toe cap
- Non-metallic penetration-resistant insole which resists penetration even by small diameter nails and other objects
- Tough VISLON® Zip and zip gusset to help stop water, dust and mud entering the boot
- Heavy duty TPU toe guard for extra scuff protection
- Scratchguard heel for added durability and extra reinforcement

PU - Polyurethane | TPU - Thermoplastic Polyurethane  
EVA - Ethel Vinyl Acetate | PUR - Polyurethane Rubber



Refer to our website for further details of the 30 day comfort guarantee and the manufacturer's 6 month warranty.

CERTIFIED TO:  
STANDARD AS  
2210.3:2019

CLASSIFICATION  
1 - ID2B15

ASTM F2413 - 18  
INCLUDING EH  
(CLAUSE 5.6)

PRODUCT CERTIFICATION



BSI Certified Product